Application No. 10/646,806 Amendment dated January 9, 2006 Reply to Office Action of October 7, 2005 Docket No.: 20140-00263-US1 YOR920000543US2

AMENDMENTS TO THE CLAIMS

1-19. (Cancelled).

20. (Previously presented) A composite structure comprising:

a substrate having a major surface; and

a resist image having a feature size of less than about 0.2 microns formed on said major surface, wherein said resist image is formed by:

providing a layer of a resist on said major surface,

lithographically exposing said resist,

immersing said exposed resist in a developing fluid thereby forming an image in said resist,

maintaining the upper surface of said image in contact with a fluid,

rinsing said resist image with a rinse fluid,

overcasting said image with a stabilizing film while said resist image remains immersed in a fluid,

displacing said fluid in contact with said overcast image with a low surface tension final displacing fluid, wherein said displacing fluid is a solvent for said film, and

removing said film and said displacing fluid by critical point drying.

- 21. (Previously presented) The composite structure, according to claim 20, wherein a replicate pattern of said resist image is transferred into said major surface.
- 22. (Previously presented) The composite structure, according to claim 21, wherein pattern transfer comprises etching.
- 23. (Previously presented) The composite structure, according to claim 21, wherein pattern transfer comprises ion implantation.

Application No. 10/646,806 Amendment dated January 9, 2006 Reply to Office Action of October 7, 2005 Docket No.: 20140-00263-US1 YQR920000543US2

BEST AVAILABLE COPY

24. (Previously presented) The composite structure, according to claim 21, wherein said substrate is a semiconductor substrate.

25. (Previously presented) A semiconductor device fabricated using the resist-semiconductor bomposite structure, according to claim 20.